

Product & Service Information

"Brand Verification"

Quality follows criteria of EN 635-2 standards

TECHNICAL



Sheet size: 1220mm X 2440mm CROSS GRAIN



2440mm X 1220mm LONG GRAIN

PACKING & LOADING

Thick	No of shts	Volume	Net Weight
3mm CG	150	1.35M3	600 kgs
5mm CG	095	1.42M3	485 kgs
5mm LG	095	1.42M3	485 kgs
6mm CG	090	1.42M3	490 kgs
6mm LG	090	1.42M3	490 kgs
8mm CG	055	1.32M3	500 kgs
8mm LG	055	1.32M3	500 kgs
16mm CG	030	1.45M3	540 kgs
Packing	approx:	36 kgs	

Sheet size:

Thickness:

Bending Radius: 3mm/3cm, 5mm/5cm, 6mm/6cm, 8mm/8cm
12mm/15cm & 16mm/20cm (Approx)

No of plies: 3mm, 5mm, 6mm & 8mm - 3 ply
12mm & 16mm - 5 ply

Density: 300kgs - 320kgs / M3 @ 12% MC

Weight per sheet: 3mm - 4kgs, 5mm - 5.1kgs, 6mm - 6.3kgs
8mm - 9.1kgs, 12mm - 14kgs & 16mm - 18kgs

Screw holding: 900 Newton

Nail holding: 55 Newton

Internal bond: 1.2 MPA

Modulus of rupture: 1.5 MPA

(Perpendicular to grain compression)

Modulus of elasticity: 85 MPA

(Perpendicular to grain compression)

Resistance - shearing 2.3 MPA



- Bottom blocks for 4 point lifting access
- Top and Bottom protection sheets
- Plastic wrapped
- Corner protection
- Plywood 4 sides LCL
- 7 strapping points
- Markings O/N, Product Type, Production Date & No, Pallet No, Client Name...



Dedicated to flexibility

**CLASS -3 ADHESIVES : EXTERIOR 1 PF RESIN
MOISTURE & WEATHER PROTECTION
IN ACCORDANCE INTERNATIONAL AND EUROPEAN
STANDARD EN 314-1,2,3**

**EMISSIONS : JIS/E0 - LOW EMISSIONS
TESTED IS 13745-1993 1.54 UNDER 3mg /100 gms**

**CE HARMONIZED STANDARDS
EN 13986:2004 & EN 636 - "G" NS**



RPP -DDS-EUTR CERTIFIED Risk Assessment Tool
European Union Timber Regulation Due Diligence System



LOADING

20FT CONTAINERS 12 PALLETS

40FT CONTAINERS 24 PALLETS

40FT HIGH CUBE 33 PALLETS

LCL PART LOADS

PACKING MATERIALS ISPM 15

**VENEERS FACE A/B PRE-SANDED 120-150 GRIT
SUPER FORM TM EDGE STAMPED AND LABELED
CG or LG+Thickness No of sheets. Every pallet is labeled CE certified**

THE PROCEDURE QUALITY ASSURANCE CONFORMITY BRANDED

Super form Tm sheets are edged stamped



"Brand Verification"



ISO:9001-2008